



AMERICAN PLASTICS

800-772-7401

Material Safety Data Sheet -Soling/Capping Material

SUPPLIER NAME:

AMERICAN PLASTICS (800-772-7401)
525 113th Street Arlington, TX 76011

Section I - Material Identification and Information

Product Name: Soling / Capping Material

Hazardous Ingredients / Identity Information: None known.

Section II: Physical/Chemical Characteristics

Characteristics:	Standard:	Units:	Test Results:
Abrasive Index	ASTM D - 1630	%	46+ / -7
Density	Hydrostatic	Grs / Cm ³	1.25 - 1.35
Hardness	ASTM D - 2240	Shore A	80 - 85
Tensile Strength	ASTM D - 412 C Kg / Cm ²		Min. 80
Elongation	ASTM D - 412	%	Min. 400
Tear Strength	ASTM D - 624 C Kg / Cm		Min. 30
Cut Growth	ASTM D - 1052	% in 100,000 cycles	0

Section III: Fire and Explosion Hazard Data

Flash Point: (method used): N/A

Flammable Limits: N/A

Extinguisher Media: Water spray

Unusual Fire & Explosion Hazards: None Known

Section IV: Reactivity Hazard Data

Stability: Stable

Conditions to Avoid: Heat & light change the appearance and color.

Incompatibility (Materials to Avoid): Avoid contact with organic fluids type: aliphatic, oxygenated, chlorinated, aromatic, fuels, oils.

Hazardous Combustion or By-Products: None known.

Section V: Health Hazard Data

Routes of Entry: Inhalation - No

Skin Absorption - No

Ingestion - Yes

Emergency & First Aid Procedures: Ingestions - Call a physician

Section VI: Precautions For Safe Handling And Use

Avoid direct flame.

Section VII: Control Measures

Respiratory protection (type): None required under normal conditions.